

SAFETY DATA SHEET

Butyl acetate

NEAR INTERNATIONAL TRADE CO.,LIMITED

- According to GHS (Sixth Revised Edition)

SDS

Section 1 Product and Company Identification

> Product Identifier

Product Name	Butyl acetate
Synonyms	n-Butyl acetate
CAS No.	123-86-4
EC No.	204-658-1
Molecular Formula	C ₆ H ₁₂ O ₂

> Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Relevant Identified Uses	Please consult manufacturer.
Uses Advised Against	Please consult manufacturer.

> Details of the Supplier of the Safety Data Sheet

Applicant Name	NEAR INTERNATIONAL TRADE CO.,LIMITED
Application Address	FLAT 1506,15/F,LUCKY CENTER,NO.165-171 WAN CHAI ROAD,WAN CHAI,HONG KONG
Applicant Post Code	25700
Applicant Telephone	+86-546-7277736
Applicant Fax	+86-546-7277736
Applicant E-mail	admin@nearchemical.cn
Manufacturer Name	NEAR INTERNATIONAL TRADE CO.,LIMITED
Manufacturer Address	FLAT 1506,15/F,LUCKY CENTER,NO.165-171 WAN CHAI ROAD,WAN CHAI,HONG KONG
Manufacturer Post Code	25700
Manufacturer Telephone	+86-546-7277736
Manufacturer Fax	+86-546-7277736
Manufacturer E-mail	admin@nearchemical.cn

> Emergency Phone Number

Emergency Phone Number	+86-546-7277736
------------------------	-----------------

Section 2 Hazards Identification

Hazard class and label elements of the product according to GHS (the sixth revised edition):

> GHS Hazard Class

Flammable Liquids Category 3
Specific Target Organ Toxicity (Single Exposure) Category 3

> GHS Label Elements

Pictogram



Signal Word

Warning

> Hazard Statements

H226 Flammable liquid and vapour
H336 May cause drowsiness or dizziness

> Precautionary Statements

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response

P312 Call a POISON CENTER/doctor, if you feel unwell.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 3 Composition/Information on Ingredients

Component	Concentration (weight percent, %)	CAS No.	EC No.
Butyl acetate	Commercial secrets	123-86-4	204-658-1

Section 4 First Aid Measures

> Description of First Aid Measures

General Advice Immediate medical attention is required. Show this safety data sheet (SDS) to

the doctor in attendance.

Eye Contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician if feel uncomfortable.

Skin Contact

Take off contaminated clothing and shoes immediately. Wash off with plenty of water for at least 15 minutes and consult a physician if feel uncomfortable.

Ingestion

Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

Inhalation

Move victim into fresh air. If breathing is difficult, give oxygen. Do not use mouth to mouth resuscitation if victim ingested or inhaled the substance. If not breathing, give artificial respiration and consult a physician immediately.

**Protecting of
First-aiders**

Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

> Most Important Symptoms and Effects, both Acute and Delayed

- 1 Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

> Indication of Any Immediate Medical Attention and Special Treatment Needed

- 1 Treat symptomatically.
- 2 Symptoms may be delayed.

Section 5 Fire Fighting Measures

> Extinguishing Media**Suitable Extinguishing
Media**

Dry chemical, carbon dioxide or alcohol-resistant foam.

**Unsuitable
Extinguishing Media**

Do not use a solid water stream as it may scatter or spread fire.

> Specific Hazards Arising from the Substance or Mixture

- 1 Will form explosive mixtures with air.
- 2 Fire exposed containers may vent contents through pressure relief valves thereby increasing fire intensity and/ or vapour concentration.
- 3 Vapours may travel to source of ignition and flash back.
- 4 Liquid and vapour are flammable.
- 5 Containers may explode when heated.
- 6 Fire exposed containers may vent contents through pressure relief valves.
- 7 May expansion or decompose explosively when heated or involved in fire.

> Advice for Firefighters

- 1 As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.
- 2 Fight fire from a safe distance, with adequate cover.
- 3 Prevent fire extinguishing water from contaminating surface water or the ground water system.

Section 6 Accidental Release Measure

> Personal Precautions, Protective Equipment and Emergency Procedures

- 1 Avoid breathing vapors and contacting with skin and eye.
- 2 Beware of vapours accumulating to form explosive concentrations.
- 3 Vapours can accumulate in low areas.

- 4 Emergency personnel wear positive pressure self-contained breathing apparatus. Wear protective and anti-static clothing. Wear chemical impermeable gloves.
- 5 Ensure adequate ventilation. Remove all sources of ignition.
- 6 Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.
- 7 Use personal protective equipment. Avoid breathing vapours, mist, gas or dust.

> Environmental Precautions

- 1 Prevent further leakage or spillage if safe to do so.
- 2 Discharge into the environment must be avoided.

> Methods and Materials for Containment and Cleaning Up

- 1 Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
- 2 Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations.
- 3 Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Section 7 Handling and Storage

> Precautions for Handling

- 1 Avoid inhalation of vapors.
- 2 Use only non-sparking tools.
- 3 To prevent fire caused by electrostatic discharge steam, equipment on all metal parts should be grounded.
- 4 Use explosion proof equipment.
- 5 Handling is performed in a well ventilated place.
- 6 Wear suitable protective equipment.
- 7 Avoid contact with skin and eyes.
- 8 Keep away from heat/sparks/open flames/ hot surfaces.
- 9 Take precautionary measures against static discharges.

> Precautions for Storage

- 1 Keep containers tightly closed.
- 2 Keep containers in a dry, cool and well-ventilated place.
- 3 Keep away from heat/sparks/open flames/ hot surfaces.
- 4 Store away from incompatible materials and foodstuff containers.

Section 8 Exposure Controls/Personal Protection

> Control Parameters

Occupational Exposure Limit Values

Component	Country/Region	Limit Value - Eight Hours		Limit Value - Short Term	
		ppm	mg/m ³	ppm	mg/m ³
Butyl acetate 123-86-4	USA - OSHA	150	710	-	-
	South Korea	150	710	200	950
	Ireland	150	710	200	950

	Germany (AGS)	62	300	124	600
	Denmark	150	710	300	1420
	Australia	150	713	200	950

Biological Limit Values

No information available

Monitoring Methods

- 1 EN 14042 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.
- 2 GBZ/T 160.1~GBZ/T 160.81-2004 Determination of toxic substances in workplace air (Series standard).

> Engineering Controls

- 1 Ensure adequate ventilation, especially in confined areas.
- 2 Ensure that eyewash stations and safety showers are close to the workstation location.
- 3 Use explosion-proof electrical/ventilating/lighting/equipment.
- 4 Set up emergency exit and necessary risk-elimination area.

> Personal Protection Equipment

Eye Protection	Tightly fitting safety goggles (approved by EN 166(EU) or NIOSH (US).
Hand Protection	Wear protective gloves (such as butyl rubber) , passing the tests according to EN 374(EU), US F739 or AS/NZS 2161.1 standard.
Respiratory protection	If exposure limits are exceeded or if irritation or other symptoms are experienced, use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges.
Skin and Body Protection	Wear fire/flare resistant/retardant clothing and antistatic boots.

Section 9 Physical and Chemical Properties

Appearance: Colorless transparent liquid	Odor: No information available
Odor Threshold: No information available	pH: No information available
Melting Point/Freezing Point (°C): -78	Initial Boiling Point and Boiling Range (°C): 126
Flash Point (°C)(Closed Cup): 27.5	Evaporation Rate: No information available
Flammability: Not applicable	Upper/lower explosive limits[%(v/v)]: Upper limit : 7.6 ; Lower limit : 1.2
Vapor Pressure (MPa): 1.2	Vapor Density (g/mL): 4.0
Relative Density (g/cm³): 0.88	Solubility: Insoluble in water
n-Octanol/Water Partition Coefficient: 1.82	Auto-Ignition Temperature(°C): 420
Decomposition Temperature (°C): No information available	Kinematic Viscosity (mm²/s): No information available
Particle characteristics: Not applicable	

Section 10 Stability and Reactivity

Reactivity	Contact with incompatible substances can cause decomposition or other chemical reactions.
Chemical Stability	Stable under proper operation and storage conditions.
Possibility of Hazardous Reactions	In contact with metal alkoxides may cause a fire.

Conditions to Avoid	Incompatible materials, heat, flame and spark.
Incompatible Materials	Metal alkyl oxide, metal hydride, inorganic peroxide, nitrate and halogens oxyacid salts.
Hazardous Decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11 Toxicological Information

> Acute Toxicity

Component	CAS No.	LD ₅₀ (Oral)	LD ₅₀ (Dermal)	LC ₅₀ (Inhalation, 4h)
Butyl acetate	123-86-4	10768mg/kg(Rat)	> 17600mg/kg(Rabbit)	No information available

> Skin Corrosion/Irritation

No information available

> Serious Eye Damage/Irritation

No information available

> Skin Sensitization

No information available

> Respiratory Sensitization

No information available

> Germ Cell Mutagenicity

No information available

> Carcinogenicity

ID	CAS No.	Component	IARC	NTP
1	123-86-4	Butyl acetate	Not Listed	Not Listed

> Reproductive Toxicity

No information available

> Reproductive Toxicity (Additional)

No information available

> STOT-Single Exposure

May cause drowsiness or dizziness(Category 3)(Butyl acetate)

> STOT-Repeated Exposure

No information available

> Aspiration Hazard

No information available

Section 12 Ecological Information

> Acute Aquatic Toxicity

Component	CAS No.	Fish	Crustaceans	Algae
Butyl acetate	123-86-4	LC ₅₀ :81mg/L (96h)(Fish)	No information available	No information available

> Chronic Aquatic Toxicity

No information available

> Others

Persistence and Degradability

No information available

Bioaccumulative Potential

No information available

Mobility in Soil

No information available

Results of PBT and vPvB Assessment

Butyl acetate does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

Section 13 Disposal Considerations

Waste Chemicals

Before disposal should refer to the relevant national and local laws and regulation. Recommend the use of incineration disposal.

Contaminated Packaging

Containers may still present chemical hazard when empty. Keep away from hot and ignition source of fire. Return to supplier for recycling if possible.

Disposal

Refer to section 13.1 and 13.2.

Recommendations

Section 14 Transport Information

Transporting Label



Marine pollutant

None

UN Number

1123

UN Proper Shipping Name

BUTYL ACETATES

Transport Hazard Class

3

Transport Subsidiary Hazard Class

None

Packing Group

III

> International Chemical Inventory

Section 15 Regulatory Information

Component	EINECS	TSCA	DSL	IECSC	NZIoC	PICCS	KECI	AICS	ENCS
Butyl acetate	√	√	√	√	√	√	√	√	√

【EINECS】 European Inventory of Existing Commercial Chemical Substances.

【TSCA】 United States Toxic Substances Control Act Inventory.

【DSL】 Canadian Domestic Substances List.

【IECSC】 China Inventory of Existing Chemical Substances.

【NZIoC】 New Zealand Inventory of Chemicals.

【PICCS】 Philippines Inventory of Chemicals and Chemical Substances.

【KECI】 Existing and Evaluated Chemical Substances.

【AICS】 Australia Inventory of Chemical Substances.

【ENCS】 Existing And New Chemical Substances.

Note

“√” Indicates that the substance included in the regulations

“x” That no data or included in the regulations

Section 16 Additional Information

Creation Date 2018/08/05

Revision Date 2018/08/05

Reason for Revision -

> Disclaimer

This Safety Data Sheet (SDS) was prepared according to UN GHS (the 6th revised edition). The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.